

CELLULAR GATEWAY

Duckfone®

Keep remote sites connected when the network isn't.

Enterprise 4G LTE cellular connectivity, secure Total Out-of-Band® access, failover, and centralized management through ZERO.



4 serial ports • Global 4G LTE • Dual SIM • PoE+

4 SERIAL PORTS
CONSOLE ACCESS

1GbE
ETHERNET

GLOBAL 4G LTE
DUAL SIM

PoE+
SIMPLE DEPLOYMENT

More than cellular connectivity.

Duckfone gives network and infrastructure teams a simple way to connect, access, and recover distributed infrastructure without replacing existing equipment.

01

Connect anything

Add primary or backup connectivity to routers, firewalls, kiosks, IoT devices and other remote endpoints.

02

Recover remotely

Use Total OOB secure access and cellular failover to diagnose and remediate issues without waiting for an onsite visit.

03

Deploy at scale

Use Zero Touch Provisioning, REST API, and ZERO cloud management across distributed fleets.

WHEN THE PRIMARY NETWORK IS UNAVAILABLE

1

ALT PATH

2

SECURE ACCESS

3

DIAGNOSE

4

RESTORE

BUILT FOR

Branch Offices • Retail • Kiosks & ATMs • IoT • Remote Sites • Temporary Locations

BUILT FOR RESILIENT NETWORKS.

I/O

Console access + Ethernet

Four Cisco straight RS-232 serial ports plus one GbE POE+ RJ45 port provide direct access to routers, switches, firewalls and other serial-managed infrastructure.

4G

Global cellular resilience

Dual-SIM Global 4G LTE provides primary or secondary WAN connectivity with carrier auto switching and failover for distributed and remote sites.

API

Automation + provisioning

Zero Touch Provisioning, REST API, and Single Sign-On through ZERO help teams deploy and manage at scale.

THE DUCKPHONE MODEL

One compact gateway. One global configuration.

MODEL	SERIAL	1GbE	4G LTE	POWER
DUCKPHONE-4-GLB	4	1 x RJ45	Yes	PoE+

Required ORAAS subscription provides ZERO Cloud Portal enrollment, warranty and technical support.

ZERO + ORAAS

Visibility beyond the gateway.

Centralize device and location visibility, serial numbers, warranty and subscription status, support coverage and fleet context through the Gearlinx ZERO cloud portal.

DEPLOY — MANAGE — MONITOR — RECOVER — MAINTAIN

TECHNICAL HIGHLIGHTS

- **Serial + Ethernet**

4 Cisco straight RS-232 serial ports and 1 x RJ45 1GbE PoE+ interface.

- **Platform memory**

50MB User Storage / 1.3GHz Qualcomm.

- **Compact enclosure**

1.57 x 4.84 x 4.80 inches; 0.66 lbs.

- **Global 4G LTE**

Dual SIM for resilient primary or secondary cellular connectivity.

- **PoE+ power**

Power over Ethernet simplifies installation and remote deployment.

- **Operating range + warranty**

-5°C to 50°C / 23°F to 122°F. Warranty included with ORAAS subscription.